



EN14351-1:2006 + A1:2010

The Window Store

Alders Way
Paignton,
Devon, TQ4 7QE
www.windowstoreplastics.co.uk



A friend in the trade™

Ref: WS001
Dated: January 2013

DECLARATION OF PERFORMANCE

PVC-U Casement Window

C(P22) – Profile 22 PVC-U Casement Window
C(24/7) – Swish Window & Door PVC-U Casement Window

Intended use: not on escape route.

Essential performance characteristics

ID	Characteristics	C(P22)	C(24/7)				
1	Resistance to wind load (EN 12210)	<i>npd</i>	<i>npd</i>				
2	Watertightness (EN 12208)	<i>npd</i>	<i>npd</i>				
3	Air permeability (EN 12207)	<i>npd</i>	<i>npd</i>				
4	Dangerous substances ¹	<i>None</i>	<i>None</i>				
5	Load-bearing capacity of safety device ²	<i>350N</i>	<i>350N</i>				
6	Acoustic performance (EN ISO 140-3)	<i>npd</i>	<i>npd</i>				
7	Thermal transmittance ³ (EN ISO 10077-1)	$\leq 1.6 W/(m^2.K)$	$\leq 1.6 W/(m^2.K)$				

BSI 0086 performed type test and issued KM 12887. ¹From statement issued by British Plastics Federation. ²Report R12269 issued by Wintech 2223 ³By calculation using EN ISO 10077-1

Declaration of conformity: I, the undersigned hereby declare conformity with the above Directive(s) and Standard(s) as shown

Signature.....

Print:Martin Connor.....

Title:Divisional IMS Manager, Epwin Group Ltd (Building Products Division).....