



EN14351-1:2006 + A1:2010

The Window Store

Alders Way
Paignton,
Devon, TQ4 7QE
www.windowstoreplastics.co.uk



A friend in the trade™

Ref: WS001
Dated: January 2013

DECLARATION OF PERFORMANCE

PVC-U Residential Doors

SL(P22) – Profile 22 Single leaf (intended use not on escape route)
SLE (P22) - Profile 22 Single leaf (intended use on escape route)

SL(24/7) – Swish Window & Door Single leaf (intended use not on escape route)
SLE (24/7) - Swish Window & Door Single leaf (intended use on escape route)

Intended use: not on escape route.

Essential performance characteristics

| ID | Characteristics | SL(P22) | SLE(P22) | SL(24/7) | SLE(24/7) | | | |
|----|---|----------------------|----------------------|----------------------|----------------------|--|--|--|
| 1 | Resistance to wind load (EN 12210) | <i>npd</i> | <i>npd</i> | <i>npd</i> | <i>npd</i> | | | |
| 2 | Watertightness (EN 12208) | <i>npd</i> | <i>npd</i> | <i>npd</i> | <i>npd</i> | | | |
| 3 | Air permeability (EN 12207) | <i>npd</i> | <i>npd</i> | <i>npd</i> | <i>npd</i> | | | |
| 4 | Dangerous substances ¹ | <i>None</i> | <i>None</i> | <i>None</i> | <i>None</i> | | | |
| 5 | Acoustic performance (EN ISO 140-3) | <i>npd</i> | <i>npd</i> | <i>npd</i> | <i>npd</i> | | | |
| 6 | Thermal transmittance ³ (EN ISO 10077-1) | $\leq 1.8 W/(m^2.K)$ | $\leq 1.8 W/(m^2.K)$ | $\leq 1.8 W/(m^2.K)$ | $\leq 1.8 W/(m^2.K)$ | | | |
| 7 | Ability to release ² | <i>None fitted</i> | <i>Pass</i> | <i>None fitted</i> | <i>Pass</i> | | | |

BSI 0086 performed type test and issued KM 505822. ¹From statement issued by British Plastics Federation. ²Certificate of Conformity 1309-CDP- 0064 issued by PIV Prufinstitut Schlosser und Beschlage Velbert ³By calculation using EN ISO 10077-1

Declaration of conformity: I, the undersigned hereby declare conformity with the above Directive(s) and Standard(s) as shown

Signature.....

Print: Martin Connor

Title: Divisional IMS Manager, Epwin Group Ltd (Building Products Division)