



EN14351-1:2006 + A1:2010

The Window Store  
Alders Way  
Paignton,  
Devon, TQ4 7QE  
www.windowstoreplastics.co.uk



Ref: WS003  
Dated: January 2013

## DECLARATION OF PERFORMANCE

PVC-U Fully Reversible Window

TS –Profile 22 Top Swing Reversible Window

Intended use: not on escape route.

### Essential performance characteristics

ID	Characteristics	TS						
1	Resistance to wind load (EN 12210)	<i>npd</i>						
2	Watertightness (EN 12208)	<i>npd</i>						
3	Air permeability (EN 12207)	<i>npd</i>						
4	Dangerous substances <sup>1</sup>	<i>None</i>						
5	Load-bearing capacity of safety device	<i>350N</i>						
6	Acoustic performance (EN ISO 140-3)	<i>npd</i>						
7	Thermal transmittance <sup>2</sup> (EN ISO 10077-1)	$\leq 1.6 W/(m^2.K)$						

BSI 0086 performed type test and issued KM 12887. <sup>1</sup>From statement issued by British Plastics Federation. <sup>2</sup>By calculation using EN ISO 10077-1

Declaration of conformity: I, the undersigned hereby declare conformity with the above Directive(s) and Standard(s) as shown

Signature: 

Print: ..... Martin Connor .....

Title: ..... Divisional IMS Manager, Epwin Group Ltd (Building Products Division) .....